

**TABLE 1**

Hole Number	Location			EOH Depth (m)	Azimuth	Dip	From	To	Length (m)	Grade (Au g/t)	Comment
	Easting	Northing	RL								
OKD-65	272519	704419	137	332	268	-55	92.0	96.5	4.5	1.0	Shear 1
							150.1	150.6	0.5	0.4	Shear 2
							<b>214.0</b>	<b>219.0</b>	<b>5.0</b>	<b>19.0</b>	<b>Shear 3</b>
							224.2	225.9	1.7	2.7	Shear 3
							<b>275.0</b>	<b>281.5</b>	<b>6.5</b>	<b>12.9</b>	<b>Shear 4</b>
OKD-66	272547	704412	138	533	267	-58	111.9	122.4	10.5	0.6	Shear 1
							179.2	183.8	4.7	0.9	Shear 2
							<b>242.8</b>	<b>244.5</b>	<b>1.7</b>	<b>33.3</b>	<b>Shear 3</b>
							248.1	249.0	0.9	3.3	Shear 3
							<b>382.4</b>	<b>388.9</b>	<b>6.5</b>	<b>15.3</b>	<b>Shear 5</b>

Widths reported are drill indicated core length. True widths are estimated at 85% to 97% of core lengths for holes OKD-65 and OKD-66. Average grades are calculated with un-capped gold assays, as insufficient drilling has been completed to determine capping levels for higher grade intercepts.