

HOLE	FROM	TO	INTERCEPT (m)	GRADE (g/t Au)	SHEAR
OKD-86	276.7	278.6	1.9	6.0	Shear 3
OKD-86	414.0	416.0	2.0	5.6	Shear 5
OKD-87A	15.00	22.80	7.8	1.7	Shear 3
OKD-88	73.8	77.0	3.1	10.8	Shear 3
OKD-88	160.5	161.5	1.0	7.8	Shear 4
OKD-89	36.0	42.3	6.3	16.4	Shear 3
OKD-89	115.7	117.7	2.0	33.4	Shear 4
OKD-90	78.2	80.3	2.1	3.9	Shear 3
OKD-90	145.4	149.9	4.5	31.5	Shear 4
OKD-91	46.5	48.0	1.5	9.4	Shear 3
OKD-91	117.0	118.0	1.0	5.1	Shear 4
OKD-92A	213.6	215.1	1.5	12.3	Shear 2
OKD-92A	319.4	323.5	4.1	8.6	Shear 3
OKD-93	263.0	266.0	3.0	6.1	Shear 3
OKD-93	398.3	400.0	1.7	13.6	Shear 5
OKD-94	9.5	11.0	1.5	7.7	Shear 3
OKD-94	22.9	24.0	1.1	8.7	Shear 3
OKD-94a	22.5	26.0	3.5	8.1	Shear 3
OKD-95	180.2	181.0	0.8	6.7	Shear 3
OKD-95	242.6	248.0	5.4	7.8	Shear 4
OKD-95	306.0	322.0	16.0	8.4	Shear 5

The intercepts reported are down-hole widths. True widths for holes 86 to 95 vary between 65% to 86% of the reported down-hole widths. Weighted average grades are calculated based on un-capped gold assays, as insufficient drilling has been completed to determine capping limits for gold assays.