

Hole ID	From	To	Length (m)	Grade (g/t Au)	Shear
OKD-116	234.9	262.0	27.1	1.4	Shear 1
OKD-117	55.5	67.8	12.3	1.5	Shear 1
OKD-117	192.0	194.4	<b>2.3</b>	<b>7.9</b>	<b>Shear 3</b>
OKD-118	34.5	42.2	7.7	2.3	Shear 1
OKD-118	161.1	162.5	<b>1.4</b>	<b>23.0</b>	<b>Shear 3</b>
OKD-118	238.4	240.9	2.5	4.8	Shear 4
OKD-118	338.0	340.5	2.5	1.9	Shear 5
OKD-119	148.0	166.0	18.0	1.9	Shear 1
OKD-119	298.0	300.9	2.9	1.1	Shear 3
OKD-119	522.5	530.9	8.4	0.6	Shear 5
OKD-120	174.2	182.0	<b>7.8</b>	<b>9.5</b>	<b>Shear 3</b>
OKD-120	396.8	418.0	21.2	0.5	Shear 5
OKD-121	157.0	180.8	23.8	0.6	Shear 1
OKD-121	305.8	311.8	<b>6.0</b>	<b>12.7</b>	<b>Shear 3</b>
OKD-121	467.1	470.7	<b>3.7</b>	<b>58.0</b>	<b>Shear 5</b>
OKD-121	569.5	570.8	<b>1.3</b>	<b>7.9</b>	<b>Shear 6</b>
OKD-122	209.0	219.0	10.0	1.6	Shear 1
OKD-122	346.0	350.3	4.3	5.7	Shear 3
OKD-122	477.8	479.6	1.8	7.9	Shear 5
OKD-123	317.5	327.0	<b>9.6</b>	<b>7.0</b>	<b>Shear 3</b>

The intercepts reported are down-hole widths. True widths of holes 116 to 123 are estimated between 72% and 87% of reported down-hole widths. Weighted average grades are calculated based on un-capped gold assays, as insufficient drilling has been completed to determine capping limits for gold assays.